


Mosaic™

Socket outlets - German standard

Cat. No(s): 0 772 10 - 6 771 20/26/27/29



0 772 10


1. USE


Socket outlets without shutters for installation in flush-mounting box, surface-mounting box, floor box, column module, desktop multi-outlet extension, office module and trunking.

2. RANGE

Description	Colour	Cat. Nos	
2 P+E socket outlet - 2 modules	White White Green Orange	0 772 10 6 771 20 6 771 26 6 771 27	
2 P+E socket outlet with flap - 2 modules	White	6 771 29	

3. DIMENSIONS (mm)





	Α	В	С	D
0 772 10 - 6 771 20/26/27	45	45	40	8.5
6 771 29	45	45	43	8.5

4. CONNECTION

Type of terminals: with screws Terminals capacity: 2 x 4 mm² Stripping length: 10 mm Screwdriver: flat 4 mm Flexible or rigid cables compatible

5. TECHNICAL CHARACTERISTICS

■ 5.1 Mechanical characteristics

Protection against solid bodies and liquids: IP 20 Protection against impacts: IK 04

■ 5.2 Material characteristics

Material: - Base: PC

- Cover plate: PC
- Halogen free
- UV resistant

Self-extinguishing:

- 850°C/30 s for insulating parts holding live parts in place
- 650°C/30 s for the other insulating part

■ 5.3 Electrical characteristics

Voltage: 250 V~

Current: 16 A

Frequency: 50-60 Hz

■ 5.4 Climatic characteristics

Storage temperature: -10° C to $+70^{\circ}$ C Operating temperature: -5° C to $+50^{\circ}$ C

6. CLEANING

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene.

Maintenance with the following products: Hexane (EN 60669-1), Methylated spirit, Soapy water, Diluted ammonia, Bleach diluted to 10%, Window-cleaning products.

Caution: A preliminary test should be carried out if other specific cleaning products are to be used.

7. STANDARDS AND APPROVALS

Compliance with standards of installation and manufacturing. Refer to e. catalogue.