

Valena™ Allure **Connected wireless control for roller shutters** and orientable sun shades

Cat. No(s): 7 525 91 - 7 526 91 - 7 527 91

7 528 91 - 7 529 91



1. USE

Zone or centralised control for wired roller shutters and orientable sun shades switches.


- Fixes directly on the wall or screws onto a flush-mounting box. Multi-gang versions can be combined with other wiring accessories.
- Fits on a piece of furniture (movable).

Can control up to 20 roller shutter switches.

2. RANGE

Description	White	lvory	Aluminium	Black	Pearl
Connected wireless control for roller shutters and orientable sun shades. Supplied complete with battery. Equipped with an LED indicator (configuration) and a RESET button (hidden) used to return to factory settings. Repositionable self-adhesive fixings supplied.	7 525 91	7 526 91	7 527 91	7 528 91	7 529 91

3. DIMENSIONS (mm)




А	В	D
90	90	14

4. OPERATION

Up when pressed at the top: - short press raises to the top - long press raises until released. $\hbox{- OSS mode: long press tilts slats}\\$ LED indicator: STOP $\hbox{-} \ useful \ during \ in stallation$ - when pressed, burst flashes red if the battery power is low. Down when pressed at the bottom: - short press lowers to the bottom



- OSS mode: long press tilts slats





Updated: 29/06/2022 Technical data sheet: F02615EN/01 Created: 13/03/2018

Valena[™] Allure Connected wireless control for roller shutters and orientable sun shades

5. TECHNICAL CHARACTERISTICS

■ 5.1 Mechanical characteristics

Protection against impacts: IK 02 Protection against solid bodies/liquids:

- IP 20 without plate and cover plate
- IP 40 for assembled product

■ 5.2 Material characteristics

Plate: ABS Sub-plate: PC Rocker plate: ABS

Mechanism with grid: Fibreglass-reinforced (10%) PC

Halogen-free UV-resistant

Self-extinguishing: 650°C/30 s

■ 5.3 Electrical characteristics

Powered by a CR2032 - 3 V lithium battery (supplied) Battery life: 8 years for 10 activations a day

ZigBee radio technology

Frequency: 2.4 GHz to 2.4835 GHz Power level: < 100 mW

■ 5.4 Climate characteristics

Usage temperature: $+ 5^{\circ}\text{C}$ to $+ 45^{\circ}\text{C}$ Storage temperature: 0°C to $+ 45^{\circ}\text{C}$

6. CARE

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene.

Resistant to the following products: Hexane (EN 60669-1), methylated spirit, soapy water, diluted ammonia, bleach diluted to 10%, window-cleaning products, pre-impregnated wipes.

The plates must not be painted.

Caution: Always test before using special cleaning products.



Take care to recycle the battery appropriately

7. ACCESSORIES

0 648 71: Repositionable adhesive for wireless control (supplied)

8. STANDARDS AND APPROVALS

The undersigned, LEGRAND, declares that the radio-electric equipment type (7 525 91 - 7 526 91 - 7 527 91 - 7 528 91 - 7 529 91) complies with directive 2014/53/EU.

The full text of the EU declaration of conformity is available on the following website: www.legrandoc.com

