


Plexo™ Electronic room thermostat

Cat. No(s): 0 695 08L



1. USE


Control for setting heating or air conditioning units.
 Sets the temperature in humid areas or special-purpose premises (workshops, laboratories, greenhouses, etc).
 Needs a power supply.
 Equipped with a push-button for summer/winter function.
 Adjustment range: 10°C to 30°C.
 Mechanism supplied with adaptor support and cover plate.
 Mechanism can be flush-mounted and surface-mounted with casing and support.

Caution: Do not install near a heat source (radiator, sunny window).

2. RANGE

Description	Grey/White
Electronic room thermostat	0 695 08L

3. DIMENSIONS (mm)




A	B	C
70.5	70.5	52

4. CONNECTION

Type of terminals: with screws
 Terminal capacity: 2 x 1.5 mm² flexible or rigid
 Stripping length: 6 mm
 Screwdriver: flat 3.5 mm

5. FUNCTION

Breaking capacity: max. 4 A.
 Adjustment range from 7°C to 30°C using the rotary knob.
 4 A normally open or closed contact.



6. TECHNICAL CHARACTERISTICS

6.1 Mechanical characteristics

Protection against solid bodies and liquids: IP 55
 Protection against impact: IK 08

6.2 Material characteristics

Support: PP + SEBS
 Mechanism casing: PC

Halogen-free
 UV-resistant

Self-extinguishing:
 850°C/30 s for insulating components holding live parts in place.
 650°C/30 s for other insulating components.

6.3 Electrical characteristics

Voltage: 230 V~
 Current: 8 A
 Frequency: 50/60 Hz

6.4 Climate characteristics

Storage temperature: -10°C to +70°C
 Usage temperature: -5°C to +40°C

Electronic room thermostat

7. CLEANING

Surface cleaning with a cloth.

Do not use: acetone, tar remover, trichloroethylene.

Maintenance with the following products: Hexane, methylated spirit, soapy water, diluted ammonia, pure bleach diluted to 10%, window-cleaning products, pre-impregnated wipes.

Caution: Always test before using other special cleaning products

8. STANDARDS AND APPROVALS

Compliant with installation and manufacturing standards.

See e-catalogue.