


SUNOTM - SEANOTM

Connected wireless control for roller shutters

Cat. No(s): 7 221 79 - 7 222 79 - 7 223 79 - 7 224 79

7 656 39 - 7 657 39 - 7 658 39 - 7 659 39



1. USE

 $\label{thm:control} Zone\ or\ centralised\ control\ for\ wired\ roller\ shutter\ switches.$


- -Fixes directly on the wall or screws onto a flush-mounting box.
- Multi-gang versions can be combined with other wiring accessories.
- -Fits on a piece of furniture (movable).

Can control up to 20 roller shutter switches.

2. RANGE

Description	Family	White	Ivory	Aluminum	Black	Dark Grey
Wireless centralized shutters remote switch	SUNO	7 221 79	7 222 79	7 223 79	7 224 79	-
	SEANO	7 656 39	-	7 657 39	7 658 39	7 659 39


3. DIMENSIONS (mm)





References	Α	В	С
7 221 79, 7 656 39	72.9	72.9	11.5

4. OPERATION









Updated: 07/05/2024 Technical data sheet: F03708EN/01 Created: 04/03/2024

Cat. No(s): 7 221 79 - 7 222 79 - 7 223 79 - 7 224 79 765639-765739-765839-765939

5. TECHNICAL CHARACTERISTICS

■ 5.1 Mechanical characteristics

Protection against impacts: IK 02 Protection against solid bodies/liquids: - IP 20 without plate and rocker plate -IP 40 for assembled product

■ 5.2 Material characteristics

Plate: ABS Sub-plate: PC Rocker plate: ABS Colours: White RAL 9003 - Ivory RAL 1013 Aluminium, Black, Dark Grey Mechanism casing with support: Fibreglass-reinforced (10 %) PC

Halogen-free

UV resistant

Self-extinguishing: 650°C/30 s

■ 5.3 Electrical characteristics

Powered by a CR2032 - 3 V lithium battery (supplied) Battery life: 8 years for 10 activations a day ZigBee radio technology frequency: 2.4 GHz to 2.4835 GHz Power level: < 100 mW Wireless mesh network, self-adaptive and secure (AES 128), conforming to standard IEEE 802.15.4 (LR-WPAN)

■ 5.4 Climatic characteristics

Usage temperature: + 5° C to + 45° C Storage temperature: 0° C to + 45° C

6. MAINTENANCE

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene. Resistant to the following products: Hexane (EN 60669-1), methylated spirit, soapy water, diluted ammonia, bleach diluted to 10%, windowcleaning products, pre-impregnated wipes.

Caution: Always test before using other special cleaning products.

Do not paint the cover plate!



Take care to recycle the battery appropriately.

7. ACCESSORIES

0 648 71: Repositionable adhesive for wireless control (x 4 supplied)

8. STANDARDS AND APPROVALS

Compliant with installation and manufacturing standards. See e-catalogue.

The undersigned, LEGRAND, declares that the radio-electric equipment type (Cat. Nos 7 221 79 - 7 222 79 7 223 79 - 7 224 79 - 7 656 39 - 7 657 39 - 7 658 39 - 7 659 39) complies with directive 2014/53/EU.The full text of the EU declaration of conformity is available on the following website: www.legrand.com/ecatalogue

